

UTILITY PATENT APPLICATION TRANSMITTAL

Submit an original and a duplicate for fee processing
(Only for new nonprovisional applications under 37 CFR §1.53(b))

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, D.C. 20231

Attorney Docket No. 200352
First Named Inventor PARKES
Express Mail No. EM196184306US

APPLICATION ELEMENTS

1. ☒ Utility Transmittal Form
2. ☒ Specification (including claims and abstract) [Total Pages 33]
3. ☒ Drawings [Total Sheets 11]
4. ☒ Combined Declaration and Power of Attorney [Total Pages 3]
 - a. ☒ Newly executed
 - b. ☐ Copy from prior application [Note Box 5 below]
 - i. ☐ Deletion of Inventor(s) Signed statement attached deleting inventor(s) named in the prior application
5. ☐ Incorporation by Reference: The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program
7. ☐ Nucleotide and/or Amino Acid Sequence Submission
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy
 - c. ☐ Statement verifying above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet and document(s))
9. ☐ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)
 - ☐ Form PTO-1449
 - ☐ Copies of References
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (Should be specifically itemized)
14. ☐ Small Entity Statement(s)
 - ☐ Enclosed
 - ☐ Statement filed in prior application; status still proper and desired
15. ☐ Certified Copy of Priority Document(s)
16. ☒ Other: A Check in the Amount of \$1202.00

17. If a **CONTINUING APPLICATION**, check appropriate box and supply the requisite information in (a) and (b) below:

- (a) ☐ Continuation ☐ Divisional ☐ Continuation-in-part of prior application Serial No. .
Prior application information: Examiner ; Group Art Unit:
- (b) Preliminary Amendment: Relate Back - 35 USC §120. The Commissioner is requested to amend the specification by inserting the following sentence before the first line:
"This is a ☐ continuation ☐ divisional of copending application(s)
☐ Serial No. , filed on .
☐ International Application, filed on , and which designates the U.S."

APPLICATION FEES

BASIC FEE				\$760.00
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	
Total Claims	38 -20=	18	x \$18.00	\$324.00
Independent Claims	4 -3=	1	x \$78.00	\$78.00
<input type="checkbox"/> Multiple Dependent Claims(s) if applicable			+ \$260.00	\$
Total of above calculations =				\$1162.00
Reduction by 50% for filing by small entity =				\$()
<input checked="" type="checkbox"/> Assignment fee if applicable			+ \$40.00	\$40.00
TOTAL =				\$1202.00


UTILITY PATENT APPLICATION TRANSMITTAL

Attorney Docket No. 200352

19. ☐ Please charge my Deposit Account No. 12-1216 in the amount of \$.
20. ☒ A check in the amount of \$1202.00 is enclosed.
21. The Commissioner is hereby authorized to credit overpayments or charge any additional fees of the following types to Deposit Account No. 12-1216:
- a. ☒ Fees required under 37 CFR §1.16.
- b. ☒ Fees required under 37 CFR §1.17.
22. ☒ The Commissioner is hereby generally authorized under 37 CFR §1.136(a)(3) to treat any future reply in this or any related application filed pursuant to 37 CFR §1.53 requiring an extension of time as incorporating a request therefor, and the Commissioner is hereby specifically authorized to charge Deposit Account No. 12-1216 for any fee that may be due in connection with such a request for an extension of time.

23. CORRESPONDENCE ADDRESS

Richard A. Wulff, Registration No. 42,238
Leydig, Voit & Mayer, Ltd.
Two Prudential Plaza, Suite 4900
180 North Stetson
Chicago, Illinois 60601-6780
Telephone: (312) 616-5600
Facsimile: (312) 616-5700

Name	Richard A. Wulff
Signature	
Date	November 9, 1999

Certificate of Mailing Under 37 CFR §1.10

I hereby certify that this Utility Patent Application Transmittal and all accompanying documents are being deposited with the United States Postal Service "Express Mail Post Office To Addressee" Service under 37 CFR §1.10 on the date indicated below and is addressed to: Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.

		November 9, 1999
Name of Person Signing	Signature	Date

A METHOD OF PIPELINED PROCESSING OF PROGRAM DATA

TECHNICAL FIELD

The invention relates generally to parallel processing techniques and, more
5 particularly, to a method of pipelined processing of program data.

BACKGROUND OF THE INVENTION

In the past few years, the speed and performance of microprocessors has
improved dramatically. Unfortunately, the speed of computer memory has not kept
10 pace with these improvements. Thus, it is often the case that a computer program
executes at the full speed of the microprocessor, only to be slowed down by frequent
reads from memory.

The use of cache memory has ameliorated this situation somewhat. Computer
systems generally keep a copy of the most recently accessed data in cache under the
15 assumption that a program will tend to make multiple accesses to the same block of
data over a short period. Thus, by storing a copy of the most recently read block of
memory in cache, the system increases the chance that subsequent blocks of data
required by the program will be located in cache. Since access to cache tends to be
much faster than access to main memory or disk, it is preferable to have as much data
20 as possible in cache.

When searching for data, most computer systems will attempt to locate the
data in cache first. If the data is not located in cache, then a "cache miss" is said to
have occurred, and the computer system will then be forced to read the data from

slower "main memory."

Simply using cache memory to store the most recently used data of an executing program was previously adequate to mask the disparity between processor speeds and main memory speeds. However, on heavily loaded systems that service multiple clients, this solution is insufficient, due to the fact that using the conventional programming model, a single thread of execution is used to perform an entire task which may include many unrelated subtasks from start to finish. Each thread tends to run on its own Central Processing Unit (CPU) and monopolize the cache of that CPU. The result of this setup is that each user thread tends to optimize the caching of its user-specific data, while competing for global data with other user threads in an inefficient, cache-destructive manner.

To illustrate the conventional method of cache utilization, reference is made to the database index tree 190 of prior art Fig. 1 and the flowchart of prior art Fig. 2.

The index tree 190 contains a set of nodes 100-132, each of which represents an alphabetical range in a database. The nodes 100-132 contain pointers 134-180. The pointers 134-164 contained in the nodes 102-116 point to other nodes, while the bottom row of nodes 118-132 contain pointers to parts of a desired data block 195. For example, the node 100 contains pointers 134 and 136, which point to the nodes 102 and 104 respectively. Additionally, the bottom row of nodes 118-132 are horizontally linked, although the linking pointers are not depicted.

The flow chart of Fig. 2 illustrates how the index tree 190 is searched using a program developed according to the conventional model. It is assumed that the desired data block 195 contains database entries starting with the letters F through Q,

5 located in cache.

that the pointer 134 links to a block of data having the range A-K, which includes part of the desired data block 195. At step 210, the conventional program determines that the node 100 is not on the bottom row. The conventional program then attempts to locate the node 102 back at step 200. Since the node 102 is not in cache, the conventional program reads the node 102 from main memory at step 204. The flow then proceeds to steps 206-209 in which the conventional program examines the pointer 142 of the node 102 to determine whether it links to the desired data block. The pointer 142 of the node 102 links to the range A-E, which does not include any part of the desired data block 195. Thus, the conventional program will then repeat steps 206-209 to examine the pointer 144. Since the pointer 144 links to the range F-K and the bottom row has not been reached the flow passes through step 210 and returns to step 200.

Upon return, the conventional program attempts to locate the node 112 at steps 200 and 202. Since the node 112 is not in cache the flow of control proceeds to step

204 in which the conventional program reads the node 112 from main memory. After the node 112 is read into cache, the conventional program examines the pointer 158 of the node 112 at steps 206-209. The pointer 158 links to the range F-G, which includes the desired data block 195. At step 210, the conventional program

5 determines that the bottom row has not been reached, and thus the conventional program returns to step 200. At step 200 the conventional program attempts to locate the node 122. Since the node 122 is not located in cache the flow proceeds to step 204 in which the conventional program reads the node 122 from main memory. Once the node 122 is read into cache the flow proceeds to steps 206-209 in which the

10 conventional program examines the pointer 170. Since the pointer 170 points to the beginning of the desired data block 195 the flow of control moves to step 210. At step 210, the conventional program determines that node 122 is on the bottom row due to the fact that it contains a pointer to the desired data block. The conventional program then proceeds to step 211, in which it determines whether there are any more

15 nodes in the bottom row. If there are no more, then the conventional program terminates. If there are more nodes, then the conventional program attempts to locate the next node in the bottom row, node 124. Since node 124 is not in cache, the conventional program reads node 124 from main memory. This process repeats until nodes 126, 128, and 130 are all read into memory and examined. At that point the

20 conventional program has located all of the nodes required to access the desired data block, and the procedure ends.

As can be seen, searching an index tree such as the index tree 190 using the conventional programming model requires a single thread to alternate between

reading a node from main memory and examining the node, resulting in a single search path through the index tree. One problem with this approach is that it discourages parallelism. If, for example, the nodes 104 and 108 had been located in cache, then the conventionally programmed search illustrated above would still have proceeded along the nodes 100, 102, 112, and 122 even though searching along the nodes 100, 104, 108 and 130 would clearly have been more efficient. It can therefore be seen that a need exists for a method of parallel programming that more effectively uses cache.

Another problem is that in a multiprocessing system, multiple users will tend to compete for resources when attempting to perform similar tasks. Prior art Fig. 3 shows an example of how two users performing simultaneous searches of a database index tree on a multiprocessor system can inadvertently compete for resources. As shown, the thread for user A executes on the CPU 301, while the thread for user B executes on the CPU 302. As in the previous example, each thread requires its CPU to alternate between reading a node and examining the node. While the user context information for each thread, (such as user-id and the program call stack) tends to remain in each of the respective caches 306 and 308, the global context information required to perform the two distinct tasks ("examine node" and "perform I/O") must be read from the main memory 304 frequently in order to keep the caches 306 and 308 coherent with main memory 304 and with each other. It can thus be seen that there is a need for a method of programming in a multiprocessor system that prevents multiple users from competing with one another for global resources.

SUMMARY OF THE INVENTION

In accordance with these needs, the present invention is realized as a method of pipelined processing. According to the method, a computer program is organized into "servers." Each server defines one or more computer-executable functions for performing a particular task in the overall program. For example, a database program could be organized into servers for buffer management, scanning index pages, scanning data pages, logging, I/O, sorting, updates, and locks.

A server generally runs as an event loop which remains in a wait state until a "work packet" or pointer thereto is received in the server's queue. A work packet is a user-defined data structure for holding data needed to perform that task. Pending work packets remain in the server's queue until they are ready to be processed by the server. A server executes until it has processed the pending work packets, at which time reverts to a wait state. Each server is capable of performing its designated task for any user on the computer system.

When a pipelined program is executed on a multiprocessor system, each CPU will seek out a server having a pending work packets. No two CPU's will be permitted to process a single server's workload unless they can do so without conflict. Thus, the general effect of this scheme will be that each CPU will tend to perform a single task for all users, thereby insuring that the global context state for each task tends to remain in the cache of the CPU performing that task. The user state information is passed from server to server within the work packets.

BRIEF DESCRIPTION OF THE DRAWINGS

PRIOR ART Figure 1 is a flow diagram of a conventional index tree;

PRIOR ART Fig. 2 is a flowchart generally depicting the steps for searching a index tree using a conventional programming technique;

5 PRIOR ART Fig. 3 is a block diagram generally depicting the flow of data in a conventionally programmed search of an index tree;

Fig. 4 is a block diagram illustrating an exemplary LAN or WAN computer system on which the present invention can reside;

Fig. 5 is a block diagram generally illustrating an exemplary architecture that
10 may be used for programming in accordance with the present invention;

Fig. 6 is a flowchart generally depicting the steps for seeking out and executing the workload of a server in accordance with the present invention;

Fig. 7 is a partial code listing of exemplary data structures which may be used to implement a packet in accordance with the present invention;

15 Fig. 8 is a flowchart generally depicting the steps taken by an exemplary node search server in accordance with the present invention;

Fig. 9 is a flowchart generally depicting the steps taken by an exemplary I/O server in accordance with the present invention;

Figs. 10-11 are a flow diagram generally depicting an exemplary movement of
20 work packets resulting from a search of an index tree in accordance with the present invention; and

PRIOR ART Fig. 12 is a flowchart generally depicting the overall path taken in a conventionally programmed search of an index tree.

65607-8799460

DETAILED DESCRIPTION OF THE INVENTION

Turning to the drawings, wherein like reference numerals refer to like elements, the invention is illustrated as being implemented in a suitable computing environment. Although not required, the invention will be described in the general context of computer-executable instructions, such as program modules, being executed by a computer. Generally, program modules include routines, programs, objects, components, data structures, etc. that perform particular tasks or implement particular abstract data types. Moreover, those skilled in the art will appreciate that the invention may be practiced with many computer system configurations, including multi-processor systems, microprocessor based or programmable consumer electronics, network PCs, minicomputers, mainframe computers, and the like. The invention may also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules may be located in both local and remote memory storage devices.

With reference to Fig. 4, an exemplary system for implementing the invention includes a general purpose computing device in the form of a conventional computer 20, including one or more central processing units or CPUs 21 processing, a system memory 22, and a system bus 23 that couples various system components including the system memory to the CPUs 21. The system bus 23 may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. The system memory includes

read only memory (ROM) 24 random access memory (RAM) 25 and a cache 19. The cache 19 may be shared among several of the CPUs 21. Additionally, each CPU 21 may have its own dedicated cache (not shown). A basic input/output system (BIOS) 26, containing the basic routines that help to transfer information between elements within the computer 20, such as during start-up, is stored in the ROM 24. The computer 20 may include one or more hard disk drives 27 for reading from and writing to one or more hard disks 60, one or more magnetic disk drives 28 for reading from or writing to one or more removable magnetic disks 29, and one or more optical disk drives 30 for reading from or writing to one or more removable optical disks 31 such as a CD ROM or other optical media.

The hard disk drives 27, magnetic disk drives 28, and optical disk drives 30 are connected to the system bus 23 by a hard disk drive interface 32, a magnetic disk drive interface 33, and an optical disk drive interface 34, respectively. The drives and their associated computer-readable media provide nonvolatile storage of computer readable instructions, data structures, program modules and other data for the computer 20. Although the exemplary environment described herein employs hard disks 60, removable magnetic disks 29, and removable optical disks 31, it will be appreciated by those skilled in the art that other types of computer readable media which can store data that is accessible by a computer, such as magnetic cassettes, flash memory cards, digital video disks, Bernoulli cartridges, random access memories, read only memories, and the like may also be used in the exemplary operating environment.

A number of program modules may be stored on the hard disks 60, magnetic

disks 29, optical disks 31, ROM 24, RAM 25, or cache 19 including an operating system 35, one or more applications programs 36, other program modules 37, and program data 38. A user may enter commands and information into the computer 20 through input devices such as a keyboard 40 and a pointing device 42. Other input
 5 devices (not shown) may include a microphone, joystick, game pad, satellite dish, scanner, or the like. These and other input devices are often connected to the processing unit 21 through a serial port interface 46 that is coupled to the system bus, but may be connected by other interfaces, such as a parallel port, game port, universal serial bus (USB), or dedicated controller. A monitor 47 or other type of display
 10 device is also connected to the system bus 23 via an interface, such as a video adapter 48. In addition to the monitor, computers typically include other peripheral output devices, not shown, such as speakers and printers.

The computer 20 may operate in a networked environment using logical connections to one or more remote computers, such as a remote computer 49. The
 15 remote computer 49 may be another computer, a server, a router, a network PC, a peer device or other common network node, and typically includes many or all of the elements described above relative to the computer 20, although only a memory storage device 50 has been illustrated in Fig. 4.

The logical connections depicted in Fig. 4 include a local area network (LAN)
 20 51 and a wide area network (WAN) 52. Such networking environments are commonplace in offices, enterprise-wide computer networks, intranets and the Internet. It will be appreciated that the network connections shown are exemplary and other means of establishing a communications link between the computers may

be used. When used in a LAN networking environment, the computer 20 is connected to the local network 51 through a network interface or adapter 53. When used in a WAN networking environment, the person computer 20 typically includes a modem 54 or other means for establishing communications over the WAN 52. The
5 modem 54, which may be internal or external, is connected to the system bus 23 via the serial port interface 46. In a networked environment, program modules depicted relative to the computer 20, or portions thereof, may be stored in the remote memory storage device 50.

In the description that follows, the invention will be described with reference
10 to acts and symbolic representations of operations that are performed by one or more computers, unless indicated otherwise. As such, it will be understood that such acts and operations, which are at times referred to as being computer-executed, include the manipulation by the processing unit of the computer of electrical signals representing data in a structured form. This manipulation transforms the data or maintains it at
15 locations in the memory system of the computer, which reconfigures or otherwise alters the operation of the computer in a manner well understood by those skilled in the art. The data structures where data is maintained are physical locations of the memory that have particular properties defined by the format of the data. However, while the invention is being described in the foregoing context, it is not meant to be
20 limiting as those of skill in the art will appreciate that various of the acts and operation described hereinafter may also be implemented in hardware.

As previously described, the conventional method of constructing a program to carry out a task on a computer forces each user thread to use a single CPU to seek

6507-8734-60

out the functions and data required for a sub-task, perform the sub-task, seek out another set of functions and data for the next sub-task, and so on. While serially executing program tasks in this manner, helps insure that the context data for the user remains in the cache for that CPU, it ignores the negative effects of swapping the
 5 global context data (the functions and data common to all user threads) required for each sub-task in and out of cache.

The invention is generally realized as a method of pipelined processing of computer program data. In accordance with the method, a computer program is divided into a series of event loops or servers, as shown in Fig. 5, in which each
 10 server performs a task of the overall program. To invoke a server, a caller passes a pointer to a queue associated with the server. The pointer references a data structure hereinafter referred to as a "work packet." The work packet contains the information required by the server to perform its particular task, including the user context data and an action code, if required. Each work packet may be structured so that it is
 15 suited for use by a particular server. Once a pointer to a work packet is passed to a server from another server, or from a main program, the functions defined in the server are performed upon the data contained in the work packet, and the results of the operations are be stored within the work packet, in a separate buffer, or other location defined by the programmer.

20 In the example of Fig. 5, a program designed to search the index tree 190 of prior art Fig. 1 is programmed as two servers: a node search server 500 for searching individual nodes and an Input/Output (I/O) server 501 for retrieving nodes of the index tree 190 from main memory. As each of the servers is repeatedly executed, one

043613-10999
 5500T-8T9E460

or more work packets 502 may be stored in queues 506 and 508 associated with the servers 500 and 501 respectively. A work packet for the node search server 500 is a data structure that may include the logical address of the node (database page number), the memory address of the buffer containing that node (if the node is in memory), a pointer to the search criteria and a pointer to a "parent" packet which request this search. An I/O work packet may contain the database page number, the memory address of buffer containing that database page after the read, an opcode (read or write) and a pointer to the parent packet (which, in this example would be one of the node search work packets) which requested the IO.

Furthermore, each server is sized so that its code and associated data structures fit into the cache 19 of each CPU 21. Although only two CPUs and caches are shown, it is understood that any number of caches and CPUs may be used for executing the two servers. To maximize the use of cache, it is preferred that each server of a pipelined program be executed on only one CPU at a time. Maintaining a one-to-one correspondence between the CPUs 21 and the servers 500 ensures cache locality and maintains cache coherency among the CPUs 21 as well as with the main memory. However, there may be some types of servers that can run on two or more CPUs at once without any risk of cache contention. To distinguish between servers that need exclusive use of a CPU and those which don't, it is preferred that each server contain a flag or other data structure which designates the sever to be *shared*, *exclusive*, or *partitioned*. A shared server may run on more than one CPU at a time. An exclusive server, in contrast, a may only be executed on a single CPU. Multiple CPUs may process the work packets of a partitioned server only if a data field in each

09436618.10999
SECRET

of the work packets falls within a predetermined range of values. For example, the I/O server 501 could be partitioned in half by database page number. One instance of the I/O server 501 running on one CPU might only process those work packets whose "destination address" fields corresponded to low memory, while another instance of the I/O server 501 running on a second CPU might only process work packets for reads to high memory. A server may receive a work packet from another server, a main program, or other calling entity. Additionally, a server may "invoke" itself by placing a work packet in its own queue. This can be done in response to some predefined event or condition, for example.

When a pipelined program runs on a computer system, each CPU may seek out and perform the work of the servers in a manner generally depicted in the flowchart of Fig. 6. As shown, a CPU waits at step 600 until at least one of the servers has at least one work packet in its queue. At step 601, the CPU determines whether the server is shared by examining a flag. If the server is shared, then the flow of control will continue at step 606. If the server is not a shared server, then the CPU determines whether another instance of the server is already running on another CPU at step 602. If no other CPU is currently processing the server's queue, then the flow will proceed to step 606. If another CPU is processing the server's queue, the CPU will determine whether the server is exclusive or partitioned by examining the server's flag.

If the server is exclusive, then the CPU searches for another server at step 600. If the server is partitioned, then the CPU reads a value of the first available work packet of the server and determines whether the value satisfies the condition for

which a multiple instance of the server may be run (i.e. the partitioning condition). If the condition is not satisfied, the CPU searches for another server having unprocessed work packets in its associated queue at step 600. If the partitioning condition is satisfied for a work packet, the flow continues at step 606. At steps 606-608, the CPU performs the operations on each work packet in the server's queue until the queue is empty. The CPU then waits for another server receive a work packet back at step 600. The steps of Fig. 6 can be rearranged and modified in many ways. For example, if the CPU finds that a work packet does not satisfy the required conditions for being processed on a partitioned server, the CPU may check other packets in the queue before attempting for locate another server.

To create a pipelined program for searching the index tree 190 of Prior art Fig. 1, the data structures of Fig. 7 may be used. The exemplary node search work packet data structure 700 and I/O server work packet 702 each inherit user context information from the structure labeled "context." The user context data may include the location of a buffer to receive the results of the search a network address to send the results to, a user ID to check access rights, and a pointer to the packet containing the original query that initiated this index tree search. A pointer 706 references the parents packet while an action code 708 tell the server whether a special function is to be performed. Such action codes may include: (1) "StartingUpSearch" to initiate an initialization procedure; (2) "StartofBatch" to cause the server to prepare for a new batch of work packets; (3) "EndofBatch" to close out processing of a batch of work packets; and (4) "ShuttingdownServer" to cause the server to exit. This list is meant to be exemplary only and there are many other specialized functions possible.

A reply state pointer 710 may be used to indicate to the processing server what action to take, if any, after the packet has been processed. Example actions include "WaitforChildren" in which the processing server is required to wait for the completion of a child work packet it created, and "WaitforEvent," which causes the server to wait for a predefined event to occur before taking any action. Additionally, the reply state may simply tell the server to generate a "Complete" signal once it has processed a work packet.

A set of user-defined fields for the node search work packet data structure 700 may include a pointer 712 to a value or range of values for which to search in the index tree nodes. For example, the pointer 712 might point to the search parameter "P-Q", indicating a search for nodes having pointers to data starting with letters between P and Q. Another user-defined field 714 might contain the number of the database page containing the node being searched. Finally, if the node being searched is in cache memory, a pointer 716 might contain the address of the page containing the node. In the I/O server packet definition 702, the user defined fields may include variables 718 and 720 for holding the database page number and memory address to which to write or from which to read.

To illustrate how a packet is processed, reference is made to Fig. 5. The node search server 500 processes node search work packets contained in its queue 506. Each node search work packet has the data structure of 700 in Fig. 7. In this example, the node search server is not required to do anything special after it consumes a node search work packet, so the reply state pointers 710 of the node search work packets may contain a value of null. To process a node search work packet, the node search

server 500 first determines whether a particular node is in cache memory by performing a hash-lookup on the page number. If the page number is not found then the node search server 500 obtains an empty I/O work packet (having the data structure of 702, Fig. 7), links it to the node search work packet and sends the empty

5 I/O work packet to the I/O server 501 as a child. The I/O work packet will have a reply state of "Complete," thus telling the I/O server to place a "complete" code in the action field of the processed I/O packet. This allows the node search server 500 to distinguish between a node search packet and a processed I/O packet. The I/O server 501 then issues an I/O request to read the specified page into cache memory and

10 "waits" for that I/O to complete before sending the I/O packet back to the node search server. While waiting for the I/O to complete, the I/O server 501 continues to process other work packets from its queue. When the I/O completes, the I/O server 501 assigns the address of the recently read-in page (containing the node required by the node search server) to the buffer pointer 719 and returns the I/O work packet to the

15 sender (i.e. the node search server 500). The node search server 500 copies the buffer address to the buffer pointer 716 of the node search packet (the parent of the I/O packet) and frees the IO packet for reuse. The processing of the of the node search packet continues with the node search server 500 searching the node located at the buffer address referred to by the pointer 719.

20 An example of how the exemplary search program of Fig. 5 may search the index tree 190 of prior art Fig. 1 is generally depicted in the flow charts of Fig. 8, 9 and 10. The steps of the node search server 500 are illustrated in Fig. 8, while those of the I/O server 501 are illustrated in Fig. 9. Although the following description will

refer back and forth to the flowcharts of Figs. 9 and 10, it will be understood that the two servers 500 and 501 can perform their respective tasks in parallel and simultaneously on two separate CPUs except when otherwise noted.

Referring to Figs. 10-11, a flow diagram generally describing the overall movement and processing of packets by the two servers is shown. In this example, it is assumed that a caller has already placed a work packet to search the index tree in the node search server queue 506, while the queue 508 of the I/O server 501 is initially empty. It is also assumed that none of the nodes of the index tree 190 is in cache initially. Finally, it is assumed that the goal of the program is identical to the goal of the prior art program depicted in prior art Fig. 2, which is to read the desired data block 195, representing database entries within the range F-Q.

At step 800 the node search server determines that there is a node search work packet in the queue. This first packet might have the action code "StartingupServer" or "StartofBatch" which would tell the node search server 500 that the first node (node 100) of the index tree 190 must be searched. The flow of control therefore, proceeds to step 802. At step 802 the node search server determines whether node 100 is in cache. Since the node 100 is not in cache, the node search server 500 obtains an empty I/O work packet (Fig. 7, data structure 702) and assigns a value of "ReadNode" to the "ActionCode" field and a value of "Complete" to the "ReplyState" parameter. These codes are only meant to illustrate how the "ReplyState" and "ActionCode" fields may be used. Many other code schemes are possible.

As depicted in front of blocks 1000 and 1020 of Fig. 10, the node search

00436618-10999
5507F-8793E460

packet queue 506 contains a partially completed packet for the node 100, while the I/O packet queue 508 now contains one unprocessed I/O packet for that node as shown at block 1020. Since there are no more unprocessed work packets in the queue 506, and since the node search work packet for node 100 is awaiting I/O, the node
 5 search server 500 returns to a wait state.

At step 918, the I/O server 501 determines if there are any outstanding I/O packets. Since there is now an unprocessed I/O work packet for the node 100 (block 1020 of Fig. 10), the I/O server reads node 100 from main memory into cache at step 920 and assigns a value to the pointer 719 (Fig. 7) which corresponds to the cache
 10 memory address of the page containing the node 100. At steps 922 the I/O server 502 copies the value contained in the "ReplyState" field to the "ActionCode" field of the I/O packet. The I/O server 502 then returns the processed I/O work packet to the node search server 500 at step 924. The flow then returns to step 918, at which point the I/O server determines that there are no other packets remaining in its queue. The
 15 I/O server 501 returns to a wait state.

The node search server 500 at step 800 detects the presence of the I/O packet and determines that the I/O packet has been completed (based on the "Complete" value in the "ActionCode" field) and therefore resumes processing the corresponding node search packet for the node 100 (block 1002 of Fig. 10). The node search server
 20 500 then determines that the node 100 is, in fact, in cache and examines the pointer 134 at step 808. At step 810, the node search server 500 determines that the pointer 134 links to the range A-K. The node search server 500 then issues a node search work packet for the node 102 at step 812. At step 814 the node search server

determines that there is another pointer within node 100 examines it at step 808. This second pointer is the pointer 136. At steps 810 and 812, the node search server 500 determines that the pointer 136 links to the range L-Z, which includes part of the desired data block 195, and thus issues an node search packet for the node 104 at step 5 812. The flow then proceeds to step 814 at which point the node search server determines that there are no more pointers in the node 100. As shown in front of block 1004 of Fig. 10, the node search packet queue now has two packets - one for node 102 and one for node 104 - that are awaiting the results of I/O work packets.

At step 800, the node search server 500 determines that there is a work packet 10 (for searching the node 102) awaiting service in the queue 506 (at block 1004). At step 802, the node search server 500 determines that the node 102 is not in cache and thus issues an I/O packet for this node at step 804. Again at steps 800 and 802 the node search server 500 identifies the work packet for the node 104, determines the node is also not in cache and issues an I/O packet for it as well. Since there are no 15 more unserved work packets in its queue, the node search server 500 reverts to a wait state.

The I/O server 501 then processes the I/O packets at steps 918 through 924 (block 1022 of Fig.10), by reading the nodes 102 and 104 into cache from main memory, supplying the appropriate buffer locations and "complete" codes and 20 returning the processed I/O packets to the node search server 500. The process then returns to step 800 of the node search server flowchart to begin the process of block 1006 of Fig. 10. At step 800 the node search server 500 determines that there is a completed I/O packet for node 102 that processing for the node 102 search packet can

0943618-11099
SECRET

resume. At step 802, node search server 500 determines that node 102 is in cache and therefore, proceeds to step 808. At step 808 the node search server retrieves the first pointer from node 102 which is the pointer 142. Since the pointer 142 links to the range A-E, the node search server does not issue an node search packet for the node 110, but rather examines the next pointer at step 808. At step 808 the node search server examines the pointer 112 and determines that it links to F-K, which is in the range of the desired data block 195. The node search server therefore issues an node search packet for the node 112 at step 812. Since this is the last pointer in node 102, the flow then returns to step 800.

At step 800, node search server 500 detects the completed I/O packet for the node 104 and resumes processing the corresponding node search packet. Since the node 104 is now in cache the flow of control proceeds to step 808. At step 808, the node search server examines the first pointer in the node 104, which is the pointer 138. Since the pointer 138 links to the range L-N, which includes the desired data block 195, the node search server 500 will issue an node search packet for the node 106 at step 812. The flow will then return to step 808. At step 808 the node search server 500 examines the next pointer in the node 104 which is the pointer 140. At step 810 the node search server 500 determines that the pointer 140 links to the range O-Z and therefore will issue a node search packet for the node 108 at step 812. Since there are no more pointers in the node 104 the flow will proceed to step 800, at which point the node search server 500 determines that there are no more unserved packets and enters a wait state. As can be seen in front of block 1008 of Fig. 10, there are now three nodes search work packets waiting for the results of I/O work packets for

nodes 108, 106, and 112.

The I/O server 501 will execute steps 918 through 924 in order to read the nodes 108, 106, and 112 into cache and return the processed I/O packets to the node search server (block 1024 of Fig. 10). The node search server 500 will then examine
 5 the nodes 108, 106, and 112 in steps 800 through 814 (block 1010 of Fig. 10), and create node search packets for nodes 130, 116, 114, 124 and 122. At this point, the state of the node search queue is shown at block 1012 of Fig. 11. Five I/O packets for these nodes will then be created by the node search server 500, processed by the I/O server 501 (block 1026 of Fig. 11), and returned to the node search server 500
 10 according to steps 918 through 924 of Fig. 9. The node search server 500 will then search the five nodes according to Fig. 8 and block 1014 of Fig. 11. These five nodes include several of the nodes from the bottom row of the index tree 190. The process will continue through blocks 1016, 1018 and 1028. After nodes 128 and 136 are read from memory and searched, the overall procedure of searching the index tree 190 will
 15 be complete.

As can be seen from Figs. 10 and 11, traversing the index tree 190 using a node search server and an I/O server causes the node search server to wait for reads from main memory on five occasions. In order to compare this result with the conventional method of prior art Fig. 2, the overall flow of the conventional search is
 20 depicted in Fig. 12. As can be seen, the conventional method results in eight waits. Additionally, having I/O requests processed in groups allows for more efficient read operations. For example, if the I/O operations initiated by several I/O packets are to different physical disks or to a disk array, the resulting reads may be performed

05436616-110999
 5507-8796450

simultaneously. Even if the reads are only to a single disk, a smart controller process the requests in such a way as the minimize head movement. In contrast, the conventional method can only read from one disk at a time, even though the data may be residing on several independent disks.

5 Furthermore, parallelism is a natural consequence of the pipelined method of programming. As discussed above in conjunction with prior art Fig. 2, the conventional method of searching the index tree 190 may not take the most efficient path to the desired data block. If nodes 104 and 108 had been located in cache, for example, the conventional method would not have taken advantage of a quicker path
10 through these nodes. The pipelined method, in contrast, would have utilized this path, in parallel with the other paths down the index tree 190.

In view of the many possible embodiments to which the principals of this invention may be applied, it should be recognized that the embodiment described herein with respect to the drawing figures is meant to be illustrative only and should
15 not be taken as limiting the scope of the invention. For example, those of skill in the art will recognize that the elements of the illustrated embodiment shown in software may be implemented in hardware and vice versa or that the illustrated embodiment can be modified in arrangement and detail without departing from the spirit of the invention. Therefore, the invention as described herein contemplates all such
20 embodiments as may come within the scope of the following claims and equivalents thereof.

CLAIMS

We claim:

1. A method of carrying out a procedure on a computer system having a memory, the memory containing user context data and global data, comprising: executing a
5 first server, wherein the first server defines a computer-executable function for performing a first sub-task of the procedure; manipulating the global data to carry out the first sub-task; sending the user context data to a second server; executing the second server, wherein the second server defines a computer-executable function for performing a second sub-task of the procedure; and manipulating the global data to
10 carry out the second sub-task using the user context data, wherein the first and second servers are optimized to execute in the cache.
2. The method of claim 1, further comprising storing the user context data in a work packet and sending the work packet from the first server to the second server,
15 wherein the work packet contains an action code for describing an action to be performed by the second server.
3. The method of claim 2, wherein the work packet contains a reply state, and the method further comprises: causing the second server to update the work packet by
20 replacing the value contained in the action code with the value contained in the reply state; and causing the second server to send the updated work packet back to the first server.

65011-21099

4. The method of claim 1, further comprising: in response to receiving a first work packet containing the user context data; causing the first server to partly perform the first sub-task using the first work packet; sending a second work packet containing the user context data from the first server to the second server; causing the second server to perform the second sub-task using the second work packet and store a result of the second sub-task in the second work packet; and sending the second work packet from the second server to the first server, wherein the result is useable by the first server to complete the performance of the first sub-task.

5. The method of claim 4, wherein the second work packet is linked as a child to the first work packet.

6. The method of claim 1, wherein the computer system has a first CPU and a second CPU, and the cache is comprised of a first area usable by the first CPU and a second area usable by the second CPU, and the executable code of the first server is optimized to fit in the first area and the executable code of the second server is optimized to fit in the second area.

7. The method of claim 1, wherein the procedure is a search of a database index tree containing a plurality of nodes, the first sub-task is to examine a node and the second sub-task is to perform an input/output operation for retrieving the node from memory and storing the node in the cache.

8. The method of claim 7, further comprising: in response to receiving a first work packet containing the user context data; causing the first server to determine if a node is in the cache; and if the node is determined not to be in the cache, sending a second work packet containing the user context data from the first server to the second server; causing the second server to retrieve the node from a main memory using the second work packet and store the node in cache; causing the second server to store a reference to the cached node in the second work packet; and sending the second work packet from the second server to the first server, wherein the first server responds to the receipt of the second work packet by searching the cached node.

9. The method of claim 8, wherein the first work packet contains a reference to a parent work packet.

10. The method of claim 1, wherein the computer system has a plurality of CPUs, and at least one server executes on only one CPU at a time.

11. The method of claim 1, wherein the computer system has a plurality of CPUs, and at least two instances of one of the servers execute concurrently on different CPUs.

12. The method of claim 1, wherein the computer system has a first CPU and a second CPU, and the work packet has a designated value, and wherein one of the servers executes on the first CPU when the designated value falls within a first range

and executes on the second CPU when the designated value falls within a second range.

13. A method of writing a computer program for carrying out a procedure on
5 computer system having a cache, global data and a user context comprising: dividing
the procedure into sub-tasks; defining a server for each sub-task, wherein each server
contains instructions for performing its respective sub-task on the global data and
wherein each server is optimized to fit inside the cache when executed; and defining a
work packet for transferring the user context between two or more of the servers.

10

14. The method of claim 13, further comprising defining an action code to be
located in the work packet for describing an action to be performed by a server.

15. The method of claim 13, further comprising defining a reply state code for the
15 work packet, the reply state code being useable by a server to gain information about
the results of a function executed by another server.

16. The method of claim 13, further comprising: defining a first work packet for a
first server; defining a second work packet for a second server, wherein the first work
20 packet is usable by the first server to perform a first sub-task on the global data and
the second work packet is usable by the second server to receive the user context from
the first server, perform the second task, and return a result of the second task to the
first server.

656077-3T333450

17. The method of claim 16, wherein the second work packet is linked as a child to the first work packet.

5 18. The method of claim 13, wherein the computer system has a first CPU and a second CPU, and the cache is comprised of a first area usable by the first CPU and a second area usable by the second CPU, and the first server is optimized to fit in the first area and the second server is optimized to fit in the second area.

10 19. The method of claim 13, wherein the procedure is a search of a database index tree containing a plurality of nodes, the first sub-task is to examine a node and the second sub-task is to perform an input/output operation for retrieving the node from memory.

15 20. The method of claim 13, wherein the computer system has a plurality of CPUs, and at least one of the servers is defined to execute on only one CPU at a time.

20 21. The method of claim 13, wherein the computer system has a plurality of CPUs and at least one of the servers is defined to run concurrently as at least two instances on different CPUs.

22. The method of claim 13, wherein the computer system has a first CPU and a second CPU, a designated value field is defined for the work packet, and wherein at

09436618-10999
5560T-8199460

least one of the servers executes on the first CPU when the designated value falls within a first range and executes on the second CPU when the designated value falls within a second range.

23. A computer-readable medium having stored thereon a data structure, the data structure comprising: a work packet for transferring user context information between at least two servers, wherein each server defines at least one function for performing a sub-task of a computer-executable procedure to manipulate a global data set

24. The computer-readable medium of claim 23, wherein the work packet has defined therein an action code for describing an action to be performed by one of the servers.

- 15 25. The computer-readable medium of claim 24, wherein the work packet has defined therein a reply state usable by one of the servers to send a result of its sub-task to another server.

26. A computer-readable medium having stored thereon a data structure, the data structure comprising: a first server defining at least one function for performing a sub-task of a computer-executable procedure to manipulate a global data set, wherein the first server executes the function in response to the receipt of a first work packet, the work packet containing user context information usable by the server to perform

the sub-task, and wherein the first server transmits the user context information to a second server using a second work packet.

27. The computer-readable medium of claim 26, wherein the second server stores
5 a result of a second sub-task performed on the global data in the second work packet and returns the second work packet to the first server.

28. A computer-readable medium having computer-executable instructions for performing, on a computer system having a memory, user context data and global
10 data, the method of claim 1.

29. The computer-readable medium of claim 28, having further computer-executable instructions for: storing the user context data in a work packet and sending the work packet from the first server to the second server, wherein the work
15 packet contains an action code for describing an action to be performed by the second server.

30. The computer-readable medium of claim 29, wherein the work packet contains a reply state, and the computer-readable medium has further computer-executable
20 instructions for: causing the second server to update the work packet by replacing the value contained in the action code with the value contained in the reply state; and causing the second server to send the updated work packet back to the first server.

655011"BT99E460

31. The computer-readable medium of claim 28, having further computer-executable instructions for: in response to receiving a first work packet containing the user context data; causing the first server to partially complete the first sub-task using the first work packet; sending a second work packet containing the user context
5 data from the first server to the second server; causing the second server to perform the second sub-task using the second work packet and store a result of the second sub-task in the second work packet; sending the second work packet to the first server, wherein the result is useable by the first server to fully complete of the first sub-task.

10 32. The computer-readable medium of claim 28, wherein the computer system has a first CPU and a second CPU, and the cache is comprised of a first area usable by the first CPU and a second are usable by the second CPU, and the executable code of the first server is optimized to fit in the first area and the executable code of the second server is optimized to fit in the second area.

15 33. The computer-readable medium of claim 28, wherein the procedure is a search of a database index tree containing a plurality of nodes, the first sub-task is to examine a node and the second sub-task is to perform an input/output operation for retrieving the node from memory and storing the node in the cache.

20 34. The computer-readable medium of claim 33 having further computer-executable instructions for: in response to receiving a first work packet containing the user context data; causing the first server to determine if a node is in the cache;

and if the node is determined not to be in the cache, sending a second work packet containing the user context data from the first server to the second server; causing the second server to retrieve the node from a main memory using the second work packet and store the node in cache; causing the second server to store a reference to the
5 cached node in the second work packet; and sending the second work packet from the second server to the first server, wherein the first server searches the cached node.

35. The computer-readable medium of claim 34, wherein the first work packet contains a reference to a parent work packet.

10 36. The computer-readable medium of claim 28, wherein the computer system has a plurality of CPUs, and at least one server executes on only one CPU at a time.

15 37. The computer-readable medium of claim 28, wherein the computer system has a plurality of CPUs, and at least two instances of one of the servers execute concurrently on different CPUs.


20 38. The computer-readable medium of claim 28, wherein the computer system has a first CPU and a second CPU, and the work packet has a designated value, and wherein one of the servers executes on the first CPU when the designated value falls within a first range and executes on the second CPU when the designated value falls within a second range.


ABSTRACT OF THE INVENTION

A system for pipelined processing of program data uses a series of servers. A server is an event loop optimized for performing a particular task in the overall program. Servers perform their respective tasks in response to receiving work packets. A work packet is a data structure containing the data needed to perform that task. Each server has a queue of pending work packets. When there are work packets in a server's queue, the server performs the required function using the user context data contained in the packet, and may generate a reply code when complete. A server may run on a single CPU until all work packets in its queue have been processed, or it may also be shared among two or more CPUs. Each server performs its designated task for all users and thus, the general effect of this method is that each CPU performs a single task for all users, thereby insuring that the global context state for each task tends to remain in the cache of the CPU performing that task.



05436618-11099
666011-8199460

PRIOR ART FIG. 1






PRIOR ART
FIG. 2



PRIOR ART
FIG. 3






FIG. 4




FIG. 5

6501-3T34450




FIG. 6





FIG. 7




FIG. 8




FIG. 9

Node search queue

Node search server

I/O queue

I/O server




FIG. 10





FIG. 11



PRIOR ART
FIG. 12

COMBINED DECLARATION AND POWER OF ATTORNEY

As below named inventor, I hereby declare that

This declaration is of the following type:

- ☒ original ☐ design ☐ supplemental
☐ national stage of PCT
☐ divisional ☐ continuation ☐ continuation-in-part

My residence, post office address, and citizenship are as stated below next to my name. I believe I am the original, first, and sole inventor (*if only one name is listed below*) or an original, first, and joint inventor (*if plural names are listed below*) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

A METHOD OF PIPELINED PROCESSING OF PROGRAM DATA

the specification of which:

- ☒ is attached hereto.
☐ was filed on _____ as Serial No. _____ and was amended on _____ (*if applicable*).
☐ was filed by Express Mail No. _____ as Serial No. not known yet, and was amended on _____ (*if applicable*).
☐ was described and claimed in PCT International Application No. _____ filed on _____ and as amended under PCT Article 19 on _____ (*if any*).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claim(s), as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed.

COUNTRY	APPLICATION	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 USC 119		
				YES	NO
				YES	NO
				YES	NO
				YES	NO

In re Application of Parke^s et al.
Serial No. not assigned

I hereby claim the benefit pursuant to Title 35, United States Code, § 119(e) of the following United States provisional application(s):

PRIOR U.S. PROVISIONAL APPLICATIONS CLAIMING THE BENEFIT UNDER 35 USC 119(e)	
APPLICATION NO.	DATE OF FILING

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56 which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application.

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 USC 120					
U.S. APPLICATIONS			Status (check one)		
U.S. APPLICATIONS	U.S. FILING DATE		PATENTED	PENDING	ABANDONED
1. 0 /					
2. 0 /					
3. 0 /					
PCT APPLICATIONS DESIGNATING THE U.S.			Status (check one)		
PCT APPLICATION NO.	PCT FILING DATE	U.S. SERIAL NOS. ASSIGNED (if any)	PATENTED	PENDING	ABANDONED
4.					
5.					
6.					

DETAILS OF FOREIGN APPLICATIONS FROM WHICH PRIORITY CLAIMED UNDER 35 USC 119 FOR ABOVE LISTED U.S./PCT APPLICATIONS				
ABOVE APPLN. NO.	COUNTRY	APPLICATION NO.	DATE OF FILING (day,month,yr)	DATE OF ISSUE (day,month,yr)
1.				
2.				
3.				
4.				

In re Application of Parke^{et} al.

Serial No. not assigned

As a named inventor, I hereby appoint the following attorneys to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

Berton Scott Sheppard, Reg. 20922
James B. Muskal, Reg. 22797
Dennis R. Schlemmer, Reg. 24703
Gordon R. Coons, Reg. 20821
John E. Rosenquist, Reg. 26356
John W. Kozak, Reg. 25117
Charles S. Oslakovic, Reg. 27583
Mark E. Phelps, Reg. 28461
H. Michael Hartmann, Reg. 28423
Bruce M. Gagala, Reg. 28844
Charles H. Mottier, Reg. 30874
John Kilyk, Jr., Reg. 30763
Robert F. Green, Reg. 27555
John B. Conklin, Reg. 30369
James D. Zalewa, Reg. 27848
John M. Belz, Reg. 30359
Brett A. Hesterberg, Reg. 31837
Jeffrey A. Wyand, Reg. 29458

Paul J. Korniczky, Reg. 32849
Pamela J. Ruschau, Reg. 34242
Steven P. Petersen, 32927
John M. Augustyn, Reg. 33589
Christopher T. Griffith, Reg. 33392
Wesley O. Mueller, Reg. 33976
Jeremy M. Jay, Reg. 33587
Jeffrey B. Burgan, Reg. 35463
Eley O. Thompson, Reg. 36035
Mark Joy, Reg. 35562
Allen E. Hoover, Reg. 37354
David M. Airan, Reg. 38811
Michael H. Tobias, Reg. 32948
Xavier Pillai, Reg. 39799
Y. Kurt Chang, Reg. 41397
Gregory C. Bays, Reg. 40505
Carol Larcher, Reg. 35243

Steven H. Sklar, Reg. 42154
M. Daniel Hefner, Reg. 41826
Thomas A. Belush, Reg. 37090
Kenneth P. Spina, Reg. 43927
Gary R. Jarosik, Reg. 35906
Song Zhu, Reg. 44420
Jeffery J. Makeever, Reg. 37390
Salim A. Hasan, Reg. 38175
Richard A. Wulff, Reg. 42238
Jamison E. Lynch, Reg. 41168
Rattan Nath, Reg. 43827
Robert M. Gould, Reg. 43642
Kevin L. Wingate, Reg. 38662
David J. Schodin, Reg. 41294
Paul L. Ahern, Reg. 17020
Theodore W. Anderson, Reg. 17035
Noel I. Smith, Reg. 18698
Katie E. Sako, Reg. 32628
Daniel D. Crouse, Reg. 32022

I further direct that correspondence concerning this application be directed to LEYDIG, VOIT & MAYER, LTD., Two Prudential Plaza, Suite 4900, 180 North Stetson, Chicago, Illinois 60601-6780, Telephone (312) 616-5600.

I hereby declare that all statements made herein of my own knowledge are true, that all statements made on information and belief are believed to be true, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor: Michael A.B. Parkes

Inventor's signature Michael A.B. Parkes

Date 11/4/99

Country of Citizenship: United Kingdom

Residence: 13320 NE 70th Street, Redmond, Washington 98052

Post Office Address: Same as above

Full name of second joint inventor, if any: Frederic O. Vicik

Inventor's signature Frederic O. Vicik

Date 10/22/99

Country of Citizenship: United States

Residence: 1203 E Lake Sammamish Shore Lane SE, Issaquah, Washington 98029

Post Office Address: Same as above